

1143774 | Fully ground HSS metal drill bit - Split point **ESSENTIAL** (Plastic sleeve)

Drill bit for the drilling of steels and cast irons, thanks to its self-centring cut





- Especially for steels and aluminiums
- Rapid drilling
- Versatile use
- Automatic centring
- Cylindrical shank
- 30° type N flute
- High-speed steel
- 118° tip

Machine

Application















P2-Weakly allied steels

Features

























Properties and benefits

- + Split-point grinding:reduction of the drill tip. Denables the simple self-centring of the drill bit on the smoothest of surfaces. Significantly reduces the requried axial load.
- Cylindrical shank: the diameter of the shank is equal to the diameter of the tip. 2 Enables versatile use on portable electrical tools and CNC machine tools.
- 30° type N flute: normal flute profile with a 30° helix angle. Suitable for general use. Provides good rigidity to the tool, as well as excellent drilling precision.
- High-speed steel: HSS substrate For general use in steels and cast irons up to 950 N/mm²
- 118° tip: 118° tip angle for the sharpening of the drill bit. Suitable for general use in materials with long shavings. Enables the rapid attach of the material and simple centring.

Sets













6 fully ground HSS metal drill bits, Split point, Ø 2 to 8 mm point, Ø 1 to 10 mm point, Ø 2 to 8 mm point, Ø 1 to 10 mm point, Ø 1 to 10 mm point point, Ø 1 to 10 mm point point, Ø 1 to 10 mm pm point Ø 1 to 10 mm point Ø

25 fully ground HSS metal drill bit - Split point Ø 1 to 13 mm by 0.5 mm

26 pieces - 25 fully ground HSS metal drill bit - Split point Ø 2 to 13 mm + 1 HSS countersinker Ø 16.5 mm



| Code | EAN | Ø | d2/CM | L | | lu QTY | PCB |
|-------------|---------------|-----|-------|----|----|----------|-----|
| 11437740100 | 3221910205904 | 1 | 1 | 34 | 13 | 2 | 6 |
| 11437740150 | 3221910205911 | 1.5 | 1.5 | 40 | 18 | 2 | 6 |
| 11437740200 | 3221910205928 | 2 | 2 | 49 | 24 | 2 | 6 |
| 11437740250 | 3221910205935 | 2.5 | 2.5 | 57 | 30 | 2 | 6 |
| 11437740300 | 3221910205942 | 3 | 3 | 61 | 33 | 2 | 6 |



1143774 | Fully ground HSS metal drill bit - Split point ESSENTIAL (Plastic sleeve)

Drill bit for the drilling of steels and cast irons, thanks to its self-centring cut

| 11437740320 | 3221910205959 | 3.2 | 3.2 | 65 | 36 | 2 | 6 |
|-------------|---------------|------|------|-----|-----|---|---|
| 11437740350 | 3221910205966 | 3.5 | 3.5 | 70 | 39 | 2 | 6 |
| 11437740400 | 3221910205973 | 4 | 4 | 75 | 43 | 2 | 6 |
| 11437740420 | 3221910205980 | 4.2 | 4.2 | 75 | 43 | 2 | 6 |
| 11437740450 | 3221910205997 | 4.5 | 4.5 | 80 | 47 | 2 | 6 |
| 11437740480 | 3221910852931 | 4.8 | 4.8 | 86 | 52 | 2 | 6 |
| 11437740500 | 3221910206000 | 5 | 5 | 86 | 52 | 2 | 6 |
| 11437740520 | 3221910852948 | 5.2 | 5.2 | 86 | 52 | 2 | 6 |
| 11437740550 | 3221910206017 | 5.5 | 5.5 | 93 | 57 | 1 | 6 |
| 11437740600 | 3221910206024 | 6 | 6 | 93 | 57 | 1 | 6 |
| 11437740620 | 3221910852955 | 6.2 | 6.2 | 101 | 63 | 1 | 6 |
| 11437740650 | 3221910206031 | 6.5 | 6.5 | 101 | 63 | 1 | 6 |
| 11437740700 | 3221910206048 | 7 | 7 | 109 | 69 | 1 | 6 |
| 11437740750 | 3221910206055 | 7.5 | 7.5 | 109 | 69 | 1 | 3 |
| 11437740800 | 3221910206062 | 8 | 8 | 117 | 75 | 1 | 3 |
| 11437740850 | 3221910206079 | 8.5 | 8.5 | 117 | 75 | 1 | 3 |
| 11437740900 | 3221910206086 | 9 | 9 | 125 | 81 | 1 | 3 |
| 11437740950 | 3221910206093 | 9.5 | 9.5 | 125 | 81 | 1 | 3 |
| 11437741000 | 3221910206109 | 10 | 10 | 133 | 87 | 1 | 3 |
| 11437741050 | 3221910206116 | 10.5 | 10.5 | 133 | 87 | 1 | 1 |
| 11437741100 | 3221910206123 | 11 | 11 | 142 | 94 | 1 | 1 |
| 11437741200 | 3221910206147 | 12 | 12 | 151 | 101 | 1 | 1 |
| 11437741300 | 3221910206161 | 13 | 13 | 151 | 101 | 1 | 1 |
| | | | | | | | |