

TIVOLY 1143872 | HSS step drill bit -TiAIN coated TivolyNorm -Helical -Split point -Tri-flat shank

High-performance drill bit for incredibly fast and intensive drilling of high-strength steels, thanks to its geometry and its TiAIN coating.





- Especially for fine high-strength steel sheets
- Maximum long life
- Incredibly fast drilling
- Optimal chip removal
- Anti-rotation attachment
- Automatic centring
- Tri-flat shank
- High-speed steel
- TiAIN coating







Machine













Application















Features

















Properties and benefits

- + Split-point grinding:reduction of the drill tip. Denables the simple self-centring of the drill bit on the smoothest of surfaces. Significantly reduces the requried axial load.
- Tri-flat shank: cylindrical shank with 3x 120° flats, for 3-piece drill chucks. December Enables maximum torque transmission Prevents the rotation of the bit in the chuck. Specially adapted for through-holes.
- High-speed steel: HSS substrate ♥ For general use in steels and cast irons up to 950 N/mm²
- TiAlN coating: TiAlN base, thickness 2/4µm, hardness 3000HV, coefficient of friction 0.4, heat resistance 900°C. ♥ Thermal shield. Allows you to increase service life, cutting speed, and progress. Reduces the axial load. Versatile uses.

Sets





3 TiAIN coated HSS step drill bits Ø 4 to 30 mm 37 mm

Related products





1143872 | HSS step drill bit -TiAIN coated TivolyNorm -Helical -Split point -Tri-flat shank

High-performance drill bit for incredibly fast and intensive drilling of high-strength steels, thanks to its geometry and its TiAIN coating.

70% biodegradable cutting oil (50 ml)



Item number M3	EAN (13 digits) M3	Drill diameter Ø	Drill diameter d3	Handle diameter or CM	Total length	Trimmed length	I3 QTY	РСВ
11438720412	3221910223083	12	4	6	65	42	1	1
11438720420	3221910223090	20	4	8	75	52	1	1
11438720430	3221910223106	30	4	10	100	77	1	1
11438720637	3221910223113	37	6	10	100	77	1	1