

1092713 | ALLCUT concrete/tile drill bit - Ground carbide cutting insert - Ribbed fluting **TECHNIC** (Plastic hanger)

Incredibly quick high-performance drill bit in rotation mode for hollow materials, tiles, steels, woods and HPL, thanks to its precise and long-lasting cut carbide cutting insert. Reduced SDS+ shank.



- Especially for tiles and earthenware
- Especially for concrete and construction materials
- Especially for hardwoods and metals
- Rotation drilling
- Incredibly fast drilling
- SDS+ shank
- High-strength steel
- Carbide cutting insert

Machine



Application



HPL panels



Hard wood



Concrete



Honeycomb brick



N- Non-ferrous alloys



P2- Weakly allied steels



Tiles

Features



Properties and benefits

- + SDS+ shank: attachment for SDS+ hammer drills (10 mm shank diameter) compliant with the SDS+ label, up to a power of 3 joules. ➡ Maximum striking power transmission for the simple and fast processing of the most difficult materials. For bits measuring 4 to 25 mm.
- + High strength steel body: body designed in a grade of steel designed for thermal processing, enabling excellent power and torque transmission. ➡ Enables optimal power and torque transmission to the head of the tool.
- + Ground carbide cutting insert: carbide cutting produced by means of a special grinding process performed on its two cutting edges, for excellent sharpness ➡ Enables the clean and precise cutting of materials. Simple centring of the tool.

Code	EAN	Ø	d2/CM	L	I	lu	QTY	PCB
1092713050160	3221912388124	5	10	160	100		1	1
1092713060160	3221912388131	6	10	160	100		1	1
1092713060210	3221912388179	6	10	210	150		1	1
1092713080160	3221912388148	8	10	160	100		1	1
1092713080210	3221912388186	8	10	210	150		1	1
1092713100160	3221912388155	10	10	160	100		1	1
1092713100260	3221912388193	10	10	260	200		1	1
1092713120160	3221912388162	12	10	160	100		1	1
1092713120260	3221912388209	12	10	260	200		1	1
1092713140260	3221912388216	14	10	260	200		1	1
1092713160260	3221912388223	16	10	260	200		1	1