



1144822 | HSS step drill bit - TiAlN coated - Helicoidal flutes -Split point - Shock serie hexa shank PREMIUM (Blister Box)


HSS step drill bit - TiAlN coated - Helicoidal flutes -Split point - Shock serie hexa shank



- Especially for fine high-strength steel sheets
- Maximum long life
- Incredibly fast drilling
- Maximum torque transmission
- Quick tool changing
- Automatic centring
- Quick-change shank
- High-speed steel
- TiAlN coating
- For impact machines



Features



Properties and benefits

- + Split-point grinding:reduction of the drill tip. ➡ Enables the simple self-centring of the drill bit on the smoothest of surfaces. Significantly reduces the required axial load.
- + Quick-Change hex attachment: a hexagonal recessed attachment for the quick locking and unlocking of the bit. Compliant with the DIN 3126 E6.3 standard ➡ Enables the quick changing of your bits by doing away with the manual tightening/loosening of the chuck. For drills and screwdrivers.
- + High-speed steel: HSS substrate ➡ For general use in steels and cast irons up to 950 N/mm²
- + TiAlN coating: TiAlN base, thickness 2/4µm, hardness 3000HV, coefficient of friction 0.4, heat resistance 900°C. ➡ Thermal shield. Allows you to increase service life, cutting speed, and progress. Reduces the axial load. Versatile uses.
- + Shock Series Impact: geometry and material specifically designed for use on high-power impact screwdrivers. ➡ Can withstand high torques, for an improved service life.



Item number M3	EAN (13 digits) M3	Drill diameter Ø	Drill diameter d3	Handle diameter or CM	Total length	Trimmed length	I3	QTY	PCB
11448220420	3221912398635	20	4	6.35	85	45		1	1
11448220430	3221912398642	30	4	6.35	115	75		1	1