

9704611 | Machine tap HSS-E5 (cobalt 5%) -M MF -NFE 66112 -B Shape (GUN) -6H -Long Series -Dulofix shank


Tap for steels. Particularly suitable for through tapping thanks to its Gun entry.



- Threading of standard Steels
- Made in Spain

- GUN entry
- 5% cobalt HSS

Machine



Application

N 1.4.1	N 1.4	P 1	P 2	P 5
N1-4-1- Aluminum-based alloy-4000 series: Silicon	N1-4-based alloy Aluminum-4000 Series: With Silicon	P1- Unrealized steels	P2- Weakly allied steels	P5- Ferritic stainless steels

Features



Properties and benefits

- + Gun entry: entry geometry consisting of facets shaped to guide debris towards the front. Improves threading efficiency and precision. ➡ Enables the clearance of debris towards the front, for the simple and precise tapping of through-holes.
- + 5% cobalt high-speed steel: HSS substrate enriched with 5% cobalt. Improved heat retention (strength, cutting sharpness) ➡ For general use in metals up to 1200 N/mm².



Code	EAN	Thread	Ø	Pitch	Norm	Drill	L	I	I4	I5	QTY	PCB
970461100400070	8420609615788	M 4	4	0,7	NFE 66112	3,30	100	20	4-4.5	2,30	1	1
970461100500080	8420609615795	M 5	5	0,8	NFE 66112	4,20	110	25	4-4.5	3,00	1	1
970461100600100	8420609615801	M 6	6	1	NFE 66112	5,00	120	27	4-4.5	3,50	1	1
970461100800125	8420609615818	M 8	8	1,25	NFE 66112	6,75	135	32	4-4.5	5,00	1	1
970461101000150	8420609615825	M 10	10	1,5	NFE 66112	8,50	150	38	4-4.5	6,00	1	1
970461101200175	8420609615832	M 12	12	1,75	NFE 66112	10,25	165	43	4-4.5	7,00	1	1