

9622011 | Standard machine tap HSS-E5 (cobalt 5%) -UNC UNF -DIN 371 -Straight -2B -Reinforced shank

Tap for short-chipping metals. Reinforced tail. Profile: UNC UNF.



■ Especially for steels and cast irons

■ 5% cobalt HSS

Machine



Application



P1-
Unrealized
steels

P2-
Weakly
allied
steels

Features



Properties and benefits

- + 5% cobalt high-speed steel: HSS substrate enriched with 5% cobalt. Improved heat retention (strength, cutting sharpness) ➡ For general use in metals up to 1200 N/mm².



Code	EAN	Thread	Ø	Pitch	Norm	Drill	L	I	I4	I5	QTY	PCB
962201100006320	8420609340314	UNC	N°6	32	DIN 371	2,85	56	11	2-3	3,00	1	1
962201100010320	8420609340369	UNF	N°10	32	DIN 371	4,10	70	14	2-3	4,90	1	1
962201100008320	8420609340338	UNC	N°8	32	DIN 371	3,50	63	12	2-3	3,40	1	1
962201100140280	8420609340413	UNF	1/4"	28	DIN 371	5,50	80	16	2-3	5,50	1	1
962201100140200	8420609340406	UNC	1/4"	20	DIN 371	5,10	80	16	2-3	5,50	1	1
962201100380240	8420609340437	UNF	3/8"	24	DIN 371	8,50	100	18	2-3	7,00	1	1
962201100380160	8420609340420	UNC	3/8"	16	DIN 371	7,90	90	18	2-3	7,00	1	1
962201100516180	8420609340444	UNC	5/16"	18	DIN 371	6,50	90	18	2-3	6,20	1	1
962201100004480		UNF	N°4	48	DIN 371	2,40	56	11	2>3	2,70	1	1
962201100010240		UNC	N°10	24	DIN 371	3,90	70	14	2>3	4,90	1	1
962201100012240		UNC	N°12	24	DIN 371	4,50	80	14	2>3	4,90	1	1
962201100516240		UNF	5/16"	24	DIN 371	6,90	90	18	2>3	6,20	1	1