

Tap for short-chipping metals. Passing tail. Profile: UNC.



■ Especially for high-strength steels, stainless steels and cast irons

■ 5% cobalt HSS

Machine



Application



P1-
Unrealized
steels

P2-
Weakly
allied
steels

Features



Properties and benefits

- + 5% cobalt high-speed steel: HSS substrate enriched with 5% cobalt. Improved heat retention (strength, cutting sharpness) ➡ For general use in metals up to 1200 N/mm².



Code	EAN	Thread	Ø	Pitch	Norm	Drill	L	I	I4	I5	QTY	PCB
962301100716200	8420609342578	UNF	7/16"	20	DIN 376	9,90	100	22	2-3	6,20	1	1
962301100120200	8420609342455	UNF	1/2"	20	DIN 376	11,50	110	25	2-3	7,00	1	1
962301100916180	8420609342615	UNF	9/16"	18	DIN 376	12,90	110	25	2-3	9,00	1	1
962301100340160	8420609342493	UNF	3/4"	16	DIN 376	17,50	125	32	2-3	11,00	1	1
962301100120130		UNF	1/2"	13	DIN 376	10,75	110	25	2>3	7,00	1	1
962301100140280		UNF	1/4"	28	DIN 376	5,50	80	16	2>3	5,50	1	1
962301100340100		UNF	3/4"	10	DIN 376	16,50	125	32	2>3	11,00	1	1
962301100516240	3221912361486	UNF	5/16"	24	DIN 376	6,90	90	18	2>3	4,90	1	1
962301100780140		UNF	7/8"	14	DIN 376	20,50	140	32	2>3	14,50	1	1
962301100916120		UNF	9/16"	12	DIN 376	12,25	110	25	2>3	9,00	1	1
962301100380240		UNF	3/8"	24	DIN 376	8,50	90	18	2>3	5,50	1	1