

High performance tapping of brass and copper alloys.



- Made in Spain
- Precise and long-lasting thread tapping
- Made in Spain
- 5% cobalt HSS

#### Machine



#### Application



N1-8-  
Aluminum-  
Series  
8000 Alloy;  
With Other  
Elements

N3-  
Copper  
alloy

#### Features



#### Properties and benefits

- + 5% cobalt high-speed steel: HSS substrate enriched with 5% cobalt. Improved heat retention (strength, cutting sharpness) ➡ For general use in metals up to 1200 N/mm<sup>2</sup>.



| Code            | EAN           | Thread    | Ø  | Pitch    | Norm  | Drill | L  | I   | I4    | I5 | QTY | PCB |
|-----------------|---------------|-----------|----|----------|-------|-------|----|-----|-------|----|-----|-----|
| 963BT1100180280 | 8420609615580 | BSPG 1/8" | 28 | DIN 5156 | 8,80  | 90    | 18 | 2-3 | 5,50  | 1  | 1   |     |
| 963BT1100140190 | 8420609615573 | BSPG 1/4" | 19 | DIN 5156 | 11,80 | 100   | 22 | 2-3 | 9,00  | 1  | 1   |     |
| 963BT1100380190 | 8420609615603 | BSPG 3/8" | 19 | DIN 5156 | 15,30 | 100   | 25 | 2-3 | 9,00  | 1  | 1   |     |
| 963BT1100120140 | 8420609615566 | BSPG 1/2" | 14 | DIN 5156 | 19,00 | 125   | 25 | 2-3 | 12,00 | 1  | 1   |     |
| 963BT1100340140 | 8420609615597 | BSPG 3/4" | 14 | DIN 5156 | 24,50 | 140   | 28 | 2-3 | 16,00 | 1  | 1   |     |
| 963BT1110000110 | 8420609615610 | BSPG 1"   | 11 | DIN 5156 | 30,80 | 160   | 36 | 2-3 | 20,00 | 1  | 1   |     |