



- Especially for aluminium
- Made in Spain
- GUN entry

Machine



Application



N- Non-ferrous alloys

Features



Properties and benefits

- + Gun entry: entry geometry consisting of facets shaped to guide debris towards the front. Improves threading efficiency and precision. ➔ Enables the clearance of debris towards the front, for the simple and precise tapping of through-holes.

Code	EAN	Thread	Ø	Pitch	Norm	Drill	L	I	I4	I5	QTY	PCB
960MT2100300050	3221912066732	M & MF 3	.5	DIN 371374376	2,50	56	10	4-5	2,70	1	1	
960MT2100400070	3221912066749	M & MF 4	0.7	DIN 371374376	3,30	63	12	4-5	3,40	1	1	
960MT2100500080	3221912066756	M & MF 5	0.8	DIN 371374376	4,20	70	12	4-5	4,90	1	1	
960MT2100600100	3221912066770	M & MF 6	1	DIN 371374376	5,00	80	15	4-5	4,90	1	1	
960MT2100800125	3221912066787	M & MF 8	1.25	DIN 371374376	6,75	90	18	4-5	6,20	1	1	
960MT2101000150	3221912066794	M & MF 10	1.5	DIN 371374376	8,50	100	22	4-5	8,00	1	1	
960MT2101200175	3221912066800	M & MF 12	1.75	DIN 371374376	10,25	110	22	4-5	7,00	1	1	
960MT2101400200	3221912066831	M & MF 14	2	DIN 371374376	12,00	110	25	4-5	9,00	1	1	
960MT2101600200	3221912066848	M & MF 16	2	DIN 371374376	14,00	110	28	4-5	9,00	1	1	