



- Threading of standard Steels
- Gradual work
- Made in Spain
- High-speed steel

Machine

Application


P1-
Unrealized
steels

Features

Properties and benefits

⊕ High-speed steel: HSS substrate ➡ For general use in steels and cast irons up to 950 N/mm²

Code	EAN	Thread	Ø	Pitch	Norm	Drill	L	I	I4	I5	QTY	PCB
950106100800075	3221912315373	MF	8	75	DIN 2181	7,25	50	18	2>6.5	4,90	1	1
950106100800100	3221912282521	MF	8	100	DIN 2181	7,00	56	22	2>6.5	4,90	1	1
950106101000100	3221912274052	MF	10	100	DIN 2181	9,00	63	18	2>6.5	9,00	1	1
950106101000125	3221912172112	MF	10	125	DIN 2181	8,80	70	24	2>6.5	8,80	1	1
950106101200100	3221912283269	MF	12	100	DIN 2181	11,00	70	20	2>6.5	11,00	1	1
950106101200125	3221912258403	MF	12	125	DIN 2181	10,80	70	20	2>6.5	10,75	1	1
950106101200150	3221912258410	MF	12	150	DIN 2181	10,50	70	20	2>6.5	10,50	1	1
950106101400125	3221912147691	MF	14	125	DIN 2181	12,80	70	22	2>6.5	12,80	1	1
950106101400150	3221912258427	MF	14	150	DIN 2181	12,50	70	22	2>6.5	12,50	1	1
950106101600150	3221912258434	MF	16	150	DIN 2181	14,50	70	22	2>6.5	14,50	1	1
950106101600200	3221912259936	MF	16	200	DIN 2181	14,00			2>6.5		1	1
950106101800150	3221912283276	MF	18	150	DIN 2181	16,50	80	22	2>6.5	16,50	1	1
950106102000150	3221912154620	MF	20	150	DIN 2181	18,50	80	22	2>6.5	18,50	1	1
950106102200150	3221912315403	MF	22	150	DIN 2181	20,50	80	22	2>6.5	20,50	1	1
950106102400150	3221912344557	MF	24	150	DIN 2181	22,50	90	22	2>6.5	22,50	1	1
950106102400200	3221912320063	MF	24	200	DIN 2181	22,00	90	22	2>6.5	22,00	1	1
950106102400300	3221912259929	MF	24	300	DIN 2181	21,00	110	45	2>6.5	21,00	1	1