

8036491 | Slotting end mill HSS-E8 (cobalt 8%) -HIGHCUT coated -DIN327D -Z2 -Hel. 30° -e8 -Short

High performance HSS-E8 slot milling cutter which gives the tool a compromise between flexibility and hardness. Versatile use. Made in France.



- Versatile use
- Superior long life
- Made in France
- 8% cobalt HSS
- HIGHCUT coating

Machine



Application



Features



Properties and benefits

- + 8% cobalt high-speed steel : HSS substrate enriched with 5% cobalt. Improved heat retention (strength, cutting sharpness). ➡ For general use in metals up to 1400 N/mm²;
- + HIGHCUT coating : Thickness 2/4µm, hardness 3200 HV, coefficient of friction 0,2, resistance to heat (400°C). ➡ High toughness. Low coefficient of friction. High wear resistance. Only for steels.



Item number M3	EAN (13 digits) M3	Cutter diameter	Handle diameter or CM	Total length	Trimmed length	Number of teeth or cutting edges z ARTICLE	Quantity No. pieces per sales unit	PCB By How Much M3
80364910200	3221910635183	2	6	48	4		1	1
80364910300	3221910635190	3	6	49	5		1	1
80364910400	3221910635206	4	6	51	7		1	1
80364910500	3221910635213	5	6	52	8		1	1
80364910600	3221910635220	6	6	52	8		1	1
80364910800	3221910635237	8	10	61	11		1	1
80364911000	3221910635244	10	10	63	13		1	1
80364911200	3221910635251	12	12	73	16		1	1
80364911400	3221910635268	14	12	73	16		1	1
80364911600	3221910635275	16	16	79	19		1	1
80364911800	3221910635282	18	16	79	19		1	1
80364912000	3221910635299	20	20	88	22		1	1