


Grooving.



- Versatile use
- Superior long life
- 8% cobalt HSS
- TiAlN coating

Application



M1-
austenitic
stainless
steels

N- Non-
ferrous
alloys

Features



Properties and benefits

- + 8% cobalt high-speed steel : HSS substrate enriched with 5% cobalt. Improved heat retention (strength, cutting sharpness). ➡ For general use in metals up to 1400 N/mm²;
- + TiAlN coating: TiAlN base, thickness 2/4µm, hardness 3000HV, coefficient of friction 0.4, heat resistance 900°C. ➡ Thermal shield. Allows you to increase service life, cutting speed, and progress. Reduces the axial load. Versatile uses.

Item number M3	EAN (13 digits) M3	Cutter diameter	Handle diameter or CM	Total length	Trimmed length	Number of teeth or cutting edges z ARTICLE	Quantity No. pieces per sales unit	PCB By How Much M3
80371310400	3221910883188	4	6	55	11	3	1	1
80371310500	3221910883195	5	6	57	13	3	1	1
80371310600	3221910883201	6	6	57	13	3	1	1
80371310800	3221910883218	8	10	69	19	3	1	1
80371311000	3221910883225	10	10	72	22	3	1	1
80371311200	3221910883232	12	12	83	26	3	1	1
80371311600	3221910883249	16	16	92	32	3	1	1
80371312000	3221910883256	20	20	104	38	3	1	1