


Grooving.



- Versatile use
- Superior long life
- 8% cobalt HSS
- TiAlN coating

Application



M1-
austenitic
stainless
steels

N- Non-
ferrous
alloys

Features



Properties and benefits

- + 8% cobalt high-speed steel : HSS substrate enriched with 5% cobalt. Improved heat retention (strength, cutting sharpness). ➡ For general use in metals up to 1400 N/mm²;
- + TiAlN coating: TiAlN base, thickness 2/4µm, hardness 3000HV, coefficient of friction 0.4, heat resistance 900°C. ➡ Thermal shield. Allows you to increase service life, cutting speed, and progress. Reduces the axial load. Versatile uses.

Item number M3	EAN (13 digits) M3	Cutter diameter	Handle diameter or CM	Total length	Trimmed length	Number of teeth or cutting edges z ARTICLE	Quantity No. pieces per sales unit	PCB By How Much M3
80371410400	3221910883263	4	6	55	11	4	1	1
80371410500	3221910883270	5	6	57	13	4	1	1
80371410600	3221910883287	6	6	57	13	4	1	1
80371410800	3221910883294	8	10	69	19	4	1	1
80371411000	3221910883300	10	10	72	22	4	1	1
80371411200	3221910883317	12	12	83	26	4	1	1
80371411600	3221910883324	16	16	92	32	4	1	1
80371412000	3221910883331	20	20	104	38	4	1	1