

8036221 | Finishing end mill HSS-E8 (cobalt 8%) -HIGHCUT coated -DIN844BK -Z3-6 -Hel. 40° - Normal

High performance HSS-E8 slot milling cutter which gives the tool a compromise between flexibility and hardness. Versatile use. Made in France.



- Versatile use
- Superior long life
- Made in France
- 8% cobalt HSS
- HIGHCUT coating

Machine



Application



Features



Properties and benefits

- + 8% cobalt high-speed steel : HSS substrate enriched with 5% cobalt. Improved heat retention (strength, cutting sharpness). ➡ For general use in metals up to 1400 N/mm²;
- + HIGHCUT coating : Thickness 2/4μm, hardness 3200 HV, coefficient of friction 0,2, resistance to heat (400°C). ➡ High toughness. Low coefficient of friction. High wear resistance. Only for steels.



Item number M3	EAN (13 digits) M3	Cutter diameter	Handle diameter or CM	Total length	Trimmed length	Number of teeth or cutting edges z ARTICLE	Quantity No. pieces per sales unit	PCB By How Much M3
80362210200	3221910632472	2	6	51	7	3	1	1
80362210300	3221910632489	3	6	52	8	3	1	1
80362210400	3221910632496	4	6	55	11		1	1
80362210600	3221910632519	6	6	57	13	4	1	1
80362210800	3221910632526	8	10	69	19	4	1	1
80362211000	3221910632533	10	10	72	22	4	1	1
80362211200	3221910632540	12	12	83	26	4	1	1
80362211400	3221910632557	14	12	83	26	4	1	1
80362211600	3221910632564	16	16	92	32	4	1	1
80362211800	3221910632571	18	16	92	32	4	1	1
80362212000	3221910632588	20	20	104	38	4	1	1