

8036231 | Finishing end mill HSS-E8 (cobalt 8%) -HIGHCUT coated -DIN844BL -Z4-6 -Hel. 40° -Long

High performance HSS-E8 slot milling cutter which gives the tool a compromise between flexibility and hardness. Versatile use. Made in France.



- Versatile use
- Superior long life
- Made in France
- 8% cobalt HSS
- HIGHCUT coating

Machine



Application



Features



Properties and benefits

- + 8% cobalt high-speed steel : HSS substrate enriched with 5% cobalt. Improved heat retention (strength, cutting sharpness). ➡ For general use in metals up to 1400 N/mm²;
- + HIGHCUT coating : Thickness 2/4µm, hardness 3200 HV, coefficient of friction 0,2, resistance to heat (400°C). ➡ High toughness. Low coefficient of friction. High wear resistance. Only for steels.



Item number M3	EAN (13 digits) M3	Cutter diameter	Handle diameter or CM	Total length	Trimmed length	Number of teeth or cutting edges z ARTICLE	Quantity No. pieces per sales unit	PCB By How Much M3
80362310400	3221910632663	4	6	63	19	4	1	1
80362310500	3221910632670	5	6	68	24	4	1	1
80362310600	3221910632687	6	6	68	24	4	1	1
80362310800	3221910632694	8	10	88	38	4	1	1
80362311000	3221910632700	10	10	95	45	4	1	1
80362311200	3221910632717	12	12	110	53	4	1	1
80362311400	3221910632724	14	12	110	53	4	1	1
80362311600	3221910632731	16	16	123	63	4	1	1
80362311800	3221910632748	18	16	123	63	4	1	1
80362312000	3221910632755	20	20	414	75	4	1	1