

Reamers left hand helix cut right hand, act as an Archimedean screw. Lubricant fed forward, no risk of scratching the part of the hole already reamed.



- **Versatile use**
- **Cylindrical shank**
- **5% cobalt HSS**

Machine



Application



Features



Properties and benefits

- + Cylindrical shank: the diameter of the shank is equal to the diameter of the tip. ➡ Enables versatile use on portable electrical tools and CNC machine tools.
- + 5% cobalt high-speed steel: HSS substrate enriched with 5% cobalt. Improved heat retention (strength, cutting sharpness) ➡ For general use in metals up to 1200 N/mm².



Code	EAN	Ø	d2	L	I	I3	QTY	PCB
80401310100	3221910647612	1	1	38	15		1	1
80401310150	3221910647629	1,5	1.5	43	26		1	1
80401310200	3221910647636	2	2	49	31		1	1
80401310250	3221910647643	2,5	2.5	57	38		1	1
80401310300	3221910647650	3	3	57	38		1	1
80401310400	3221910647674	4	4	75	50		1	1
80401310500	3221910647698	5	5	86	59		1	1
80401310550	3221910647704	5,5	5.6	93	65		1	1
80401310600	3221910647711	6	5.6	101	71		1	1
80401310650	3221910647728	6,5	6.3	101	71		1	1
80401310700	3221910647735	7	7.1	109	78		1	1
80401310800	3221910647759	8	8	117	84		1	1
80401310900	3221910647773	9	9	125	88		1	1
80401310950	3221910647780	9,5	10	125	88		1	1
80401311000	3221910647797	10	10	133	97		1	1
80401311100	3221910647803	11	10	133	97		1	1
80401311200	3221910647810	12	10	151	110		1	1
80401311300	3221910647827	13	10	151	110		1	1
80401311400	3221910647834	14	12.5	160	114		1	1
80401311500	3221910647841	15	12.5	162	115		1	1
80401311600	3221910647858	16	12.5	170	120		1	1
80401311700	3221910647865	17	14	175	123		1	1

Reamers left hand helix cut right hand, act as an Archimedean screw. Lubricant fed forward, no risk of scratching the part of the hole already reamed.

80401311800	3221910647872	18	14	182	132	1	1
80401311900	3221910647889	19	16	159	140	1	1
80401312000	3221910647896	20	16	195	150	1	1