

## 1T50242 | Jigsaw blade - For worktop - T attachment TECHNIC (Blister)

Bi-metal, the perfect combination of flexibility (HSS "spring" steel), and durability (welded HSS teeth). Head treated in a vacuum furnace. Suitable for wood & metal working.



- Cross ground, tapered
- Inverted toothing
- HSS toothing



### Machine



### Application



Worktop

### Features



### Properties and benefits

- + Cross ground, tapered: each tooth is perpendicular to the cutting axis, is aligned, and cuts along its entire width. The sides and the back are tapered. ⚙️ Enables fast and straight cutting. The blade does not come back into contact with the material and enables a fine and clean cut.
- + Inverted toothing: blade whereby the teeth cut while moving downward. Inverted teeth: blade whereby the teeth cut while moving downwards. ⚙️ Enables clean cuts without splinters on the top side. For an optimal result, disable the machine's pendulum function.
- + Bi-metal steel blade: combination of progressive toothing made from quick-cutting tempered steel (HSS), and the body made from high-strength carbon steel (HCS). ⚙️ Very flexible, used when there is a risk that the attachment will break. Very high resistance to wear, for a longer service life.



| Code        | EAN           | Cutting thickness | Cutting type | Sawing cutting quality | L   | I  | Pitch | QTY | PCB |
|-------------|---------------|-------------------|--------------|------------------------|-----|----|-------|-----|-----|
| XT505520012 | 3221910898557 | 3-50              | Straight cut | Finishing              | 100 | 75 | 2.5   | 2   | 3   |