

1T50592 | Jigsaw blade - For parquet - U attachment TECHNIC (Blister)

Bi-metal, the perfect combination of flexibility (HSS "spring" steel), and durability (welded HSS teeth). Head treated in a vacuum furnace. Suitable for wood & metal working.



- Cross ground, tapered
- Pointed tothing
- HSS tothing



Machine



Application




Parquet

Features



Properties and benefits

- + Cross ground, tapered: each tooth is perpendicular to the cutting axis, is aligned, and cuts along its entire width. The sides and the back are tapered. ➡ Enables fast and straight cutting. The blade does not come back into contact with the material and enables a fine and clean cut.
- + Pointed tothing: design whereby the teeth are positioned horizontally to the body of the blade. ➡ Enables clean cutting quality, with no splinters on either side. For an optimal result, disable the machines pendulum function.
- + Bi-metal steel blade: combination of progressive tothing made from quick-cutting tempered steel (HSS), and the body made from high-strength carbon steel (HCS). ➡ Very flexible, used when there is a risk that the attachment will break. Very high resistance to wear, for a longer service life.



Code	EAN	Cutting thickness	Cutting type	Sawing cutting quality	L	I	Pitch	QTY	PCB
XT505320039	3221910898168	3-30	Straight cut	Finishing	100	75	2	2	3
XT505320040	3221910898175	1.5-15	Curved cut	Finishing	100	75	2	2	3