

XT51032 | Reciprocating saw blade - Multi-material - Universal attachment TECHNIC (Carton sleeve)

Bi-metal, the perfect combination of flexibility (HSS "spring" steel), and durability (welded HSS teeth). Head treated in a vacuum furnace. Suitable for wood & metal working.



- Milled, set
- HSS toothing
- Variable teeth



Machine



Application



Multi-material

Features



Properties and benefits

- + Milled, set: blade for somewhat crude cutting into hard and soft wood, aluminium, plastic materials, and non-ferrous metals. ⚙️ Enables the rapid progression of the blade into hard and soft wood, aluminium, plastic materials, and non-ferrous metals.
- + Bi-metal steel blade: combination of progressive toothing made from quick-cutting tempered steel (HSS), and the body made from high-strength carbon steel (HCS). ⚙️ Very flexible, used when there is a risk that the attachment will break. Very high resistance to wear, for a longer service life.
- + Variable toothing: design whereby the teeth are positioned with irregular gaps (pitches) and with alternating small and large teeth with different gap sizes. ⚙️ Enables the cutting of a wide range of different materials. Reduces the risk of teeth breaking and reduces vibrations when cutting.



Code	EAN	Cutting thickness	Cutting type	Sawing cutting quality	L	I	Pitch	QTY	PCB
XT505820104	3221910898380	3-150	Straight cut	Quick Cut	200	180		2	1
XT505820105	3221910898397	3-100	Straight cut	Quick Cut	150	130		2	3
XT5058201043	3221912400475			Quick Cut					1