

XT50102 | Cutting disc - For wood and wood with embedded nails - For grinder ESSENTIAL (Carton sleeve)

For the rough carving, notching wood, the ageing of beams. To be used by experienced people, within a completely secure environment.



- Alternate bevel tooth ATB
- Demolition toothing (ATB)
- Anti-kickback heel



Machine



Application



Wood with nails

Features



Properties and benefits

- + Alternate bevel teeth (ATB): bevelled teeth on the upper side, alternatively on the right and on the left. ➡ Ideal for longitudinal and transverse cuts. Suitable for universal use in hard and soft woods, chipboard ...
- + Demolition toothing (ATB): carbide teeth with a lower hardness, protruding slightly beyond the body of the blade. ➡ Absorbs impact. For wood, including wood with nails fully embedded, staples, pieces of concrete...
- + Anti-kickback heel: the presence of an anti-kickback heel is vital. They are located at the back of the teeth. ➡ Limits the quantity of material removed by each tooth of the blade. Thus prevents excessive cutting effort and eliminates wood emissions.



Code	EAN	Blade diameter	d2 Bore	Z	Reduction ring Ø	E1	E2	Max. rotation speed	QTY	PCB
XT50512004535	3128820045357	115	22.2	12		1.5	0	11600	1	1
XT50512004545	3128820045456	125	22.2	12		1.5	0	10700	1	1
XT50512004555	3221912006363	180	22.2	12		1.5	0	7400	1	1