

Particularly well-suited for the quick and clean sawing of wood.




- Alternate bevel tooth ATB
- ATB toothing
- Expansion slots
- Anti-kickback heel



#### Machine



#### Application



#### Features



#### Properties and benefits

- + Alternate bevel teeth (ATB): bevelled teeth on the upper side, alternatively on the right and on the left. ➡ Ideal for longitudinal and transverse cuts. Suitable for universal use in hard and soft woods, chipboard ...
- + ATB toothing with a positive angle of attack. Teeth angled towards the front. ➡ Enables more aggressive work.
- + Expansion slots: these are distributed along the outer edges of the disc. ➡ They allow the metal to expand when it heats as a result of friction, thus avoiding the deformation of the blade.
- + Anti-kickback heel: the presence of an anti-kickback heel is vital. They are located at the back of the teeth. ➡ Limits the quantity of material removed by each tooth of the blade. Thus prevents excessive cutting effort and eliminates wood emissions.

#### Related products



Saw guide



| Code          | EAN           | Blade diameter | d2 Bore | Z  | Reduction ring Ø | E1  | E2   | Max. rotation speed | QTY | PCB |
|---------------|---------------|----------------|---------|----|------------------|-----|------|---------------------|-----|-----|
| XT50514004121 | 3128820041212 | 125            | 20      | 20 | 10+12,7          | 1.5 | 2.45 | 7500                | 1   | 1   |
| XT50514004123 | 3221912006370 | 160            | 30      | 20 | 20               | 1.5 | 2.45 | 7000                | 1   | 1   |
| XT50514004126 | 3128820041267 | 130            | 20      | 20 | 16               | 1.5 | 2.45 | 7500                | 1   | 1   |
| XT50514004136 | 3128820041366 | 140            | 20      | 20 | 10+12,7+16       | 1.5 | 2.45 | 7500                | 1   | 1   |
| XT50514004148 | 3128820041489 | 150            | 20      | 20 | 16               | 1.5 | 2.45 | 7500                | 1   | 1   |
| XT50514004163 | 3128820041632 | 160            | 20      | 20 | 16               | 1.5 | 2.45 | 7000                | 1   | 1   |
| XT50514004171 | 3128820041717 | 180            | 30      | 24 | 20               | 1.6 | 2.6  | 7000                | 1   | 1   |
| XT50514004172 | 3128820041724 | 180            | 20      | 24 | 16               | 1.6 | 2.6  | 7000                | 1   | 1   |
| XT50514004175 | 3221912076311 | 184            | 16      | 24 |                  | 1.6 | 2.6  | 7000                | 1   | 1   |

Particularly well-suited for the quick and clean sawing of wood.

|                             |     |    |    |         |          |      |   |   |
|-----------------------------|-----|----|----|---------|----------|------|---|---|
| XT50514004182 3221912076328 | 190 | 16 | 24 |         | 1.7 2.8  | 7000 | 1 | 1 |
| XT50514004184 3128820041847 | 184 | 20 | 24 | 16      | 1.6 2.6  | 7000 | 1 | 1 |
| XT50514004431 3128820044312 | 170 | 20 | 20 | 16      | 1.5 2.45 | 7000 | 1 | 1 |
| XT50514004432 3128820044329 | 190 | 20 | 24 | 16      | 1.7 2.8  | 7000 | 1 | 1 |
| XT50514004434 3128820044343 | 190 | 30 | 24 | 20      | 1.7 2.8  | 7000 | 1 | 1 |
| XT50514004435 3128820044350 | 210 | 30 | 24 | 20+25,4 | 1.7 2.8  | 6500 | 1 | 1 |
| XT50514004436 3128820044367 | 230 | 30 | 24 | 20      | 1.8 2.85 | 6500 | 1 | 1 |
| XT50514004438 3128820044381 | 235 | 30 | 24 | 25      | 1.8 2.85 | 6500 | 1 | 1 |
| XT50514004453 3128820044534 | 250 | 30 | 30 | 20      | 1.5 2.45 | 5500 | 1 | 1 |
| XT50514004125 3221912261069 | 165 | 16 | 24 |         | 1.5 2.45 | 7000 | 1 | 1 |
| XT50514004130 3221912362582 | 165 | 20 | 20 | 16      | 1.5 2.45 | 7000 | 1 | 1 |