

# 11455070015 | 19 HSS-E5 metal drill bit (5% cobalt) - SLR graduated - Split point - Ø 1 to 10 mm by 1/2

Rapid drill bit for the drilling of steels, stainless steels, and cast irons.



- Especially for high-strength steels, stainless steels and cast irons
- Tough
- Rapid drilling
- Versatile use
- Automatic centring
- Cylindrical shank
- 30° type N flute
- 5% cobalt HSS
- 135° tip

Ø 1 - 1.5 - 2 - 2.5 - 3 - 3.5 - 4 - 4.5 - 5 - 5.5 - 6 - 6.5 - 7 - 7.5 - 8 - 8.5 - 9 - 9.5 - 10 mm -TIVOLY BOX Case



**Application** 



#### Machine



















P3- strong alloy steels

## Features























# Properties and benefits

- + Split-point grinding:reduction of the drill tip. Enables the simple self-centring of the drill bit on the smoothest of surfaces. Significantly reduces the requried axial load.
- → Cylindrical shank: the diameter of the shank is equal to the diameter of the tip. 
  Enables versatile use on portable electrical tools and CNC machine tools.
- + 30° type N flute: normal flute profile with a 30° helix angle. Suitable for general use. Provides good rigidity to the tool, as well as excellent drilling precision.
- + 5% cobalt high-speed steel: HSS substrate enriched with 5% cobalt. Improved heat retention (strength, cutting sharpness) ❖ For general use in metals up to 1200 N/mm².
- + 135° tip: 135° tip angle for the sharpening of the drill bit. Suitable for strong and difficult materials. Enables a shorter and stronger cutting edge, thus prolonging the service life.

### Données de gestion :

PCB: 1 / Kilogram.: 0,568 / Dimensions: 0180x0140x0043 mm / EAN: 3221912016522