



- Especially for fine high-strength steel sheets
- Maximum long life
- Optimal chip removal
- Incredibly fast drilling
- Especially for the Shock Series

- Automatic centring
- Quick-change shank
- High-speed steel
- TiAlN coating
- For impact machines



Features



Properties and benefits

- + Split-point grinding:reduction of the drill tip. ➡ Enables the simple self-centring of the drill bit on the smoothest of surfaces. Significantly reduces the required axial load.
- + Quick-Change hex attachment: a hexagonal recessed attachment for the quick locking and unlocking of the bit. Compliant with the DIN 3126 E6.3 standard ➡ Enables the quick changing of your bits by doing away with the manual tightening/loosening of the chuck. For drills and screwdrivers.
- + High-speed steel: HSS substrate ➡ For general use in steels and cast irons up to 950 N/mm²
- + TiAlN coating: TiAlN base, thickness 2/4µm, hardness 3000HV, coefficient of friction 0.4, heat resistance 900°C. ➡ Thermal shield. Allows you to increase service life, cutting speed, and progress. Reduces the axial load. Versatile uses.
- + Shock Series Impact: geometry and material specifically designed for use on high-power impact machines. ➡ Resistant to high tightening torques and can handle all seized screws and bolts.

Données de gestion :

PCB : 1 / Kilogram. : 0,001 / Dimensions : 0001x0001x0001 mm / EAN : 3221912398659