11901170066 | Set of 5 speed point wood drills Ø 2 to 5mm + 5 graduated SLR cross-point metal drills HSS-E5 (Cobalt 5%) Ø 1 to 3mm

High-performance drill with speed point grinding and HSS substrate for fast, accurate drilling in the hardest woods. SLR scale for depth control. Suitable for angled drilling. High-performance drill for ultra-fast, intensive drilling of stainless steels thanks to its cobalt substrate and sharpening. SLR graduation for depth control. Made in France.

- **Especially for hardwoods and terraces**
- **Incredibly fast drilling**
- **Maximum long life**
- **Especially for stainless steel and high-strength steels**
- **Made in France**

- Automatic centring
- Tri-flat shank
- 5% cobalt HSS
- SPEED-POINT tip
- SLR laser graduation

Set of 5 speed point wood drills Ø 2- 2.5- 3- 4- 5mm+ 5 HSS-E5 (Cobalt 5%) graduated SLR cross-point metal drills Ø 1- 1.5- 2- 2.5- 3mm

Machine

Application

Cast iron | Hard wood | M- Stainless steels | P2- Weakly allied steels | Terrace | Laminated wood

Properties and benefits

- Split-point grinding:reduction of the drill tip. ➔ Enables the simple self-centring of the drill bit on the smoothest of surfaces. Significantly reduces the requried axial load.
- Tri-flat shank: cylindrical shank with 3x 120° flats, for 3-piece drill chucks. ➔ Enables maximum torque transmission Prevents the rotation of the bit in the chuck. Specially adapted for through-holes.
- 5% cobalt high-speed steel: HSS substrate enriched with 5% cobalt. Improved heat retention (strength, cutting sharpness) ➔ For general use in metals up to 1200 N/mm².
- SPEED-POINT tip: Special TIVOLY grinding bit, for simple centring, and an attack and exit without splinters. ➔ Enables incredible fast drilling, and drilling at an angle, without a guide and with no slippage.
- SLR laser graduation: laser graduation on the cutting part of the drill bit. ➔ Laser graduation allows you to control your drilling depth while the bit is rotating.

Données de gestion :

PCB : 1 / **Kilogram. :** 0,095 / **Dimensions :** 0150x0050x0035 mm / **EAN :** 3221912400376